

# NANLITE

PavoTubes	NanLite PavoTube 30C 4 ft RGBW LED Tube with Internal Battery	NanLite PavoTube 30C 4 ft RGBW LED Tube with Internal Battery 2 Light Kit	NanLite PavoTube 30C 4 ft RGBW LED Tube with Internal Battery 4 Light Kit	NanLite PavoTube 15C 2 ft RGBW LED Tube with Internal Battery	NanLite PavoTube 15C 2 ft RGBW LED Tube with Internal Battery 2 Light Kit	NanLite PavoTube 15C 2 ft RGBW LED Tube with Internal Battery 4 Light Kit
Product Weight (lb)	2.6	5.3	10.6	1.9	3.7	7.5
Product Length (in)	46	46	46	30	30	30
Product Diameter (in)	1.9	1.9	1.9	1.9	1.9	1.9
Color Temp (Kelvin)	2700K-6500K	2700K-6500K	2700K-6500K	2700K-6500K	2700K-6500K	2700K-6500K
CRI	98	98	98	98	98	98
TLCI	95	95	95	95	95	95
Lux @ 1m 2700K	633 Lux	633 Lux	633 Lux	375 Lux	375 Lux	375 Lux
Lux @ 2m 2700K	194Lux	194Lux	194Lux	99Lux	99Lux	99Lux
Lux @ 3m 2700K	101Lux	101Lux	101Lux	46Lux	46Lux	46Lux
Lux @ 1m 3200K	508	973	1869	330	489	976
Lux @ 2m 3200K	142	296	589	103	145	281
Lux @ 3m 3200K	67	143	294	53	69	137
Accepts Grids	No	No	No	Yes	Yes	
Lux @ 1m 5600K	631	1228	2369	352	635 (two tubes combined)	1216 (4 tubes combined)
Lux @ 2m 5600K	179	378	744	105	175 (two tubes combined)	346 (4 tubes combined)
Lux @ 3m 5600K	83	187	369	54	84 (two tubes combined)	170 (4 tubes combined)
Lux @ 1m 6500K	719Lux	719Lux	719Lux	430 Lux	430 Lux	430 Lux
Lux @ 2m 6500K	209Lux	209Lux	209Lux	117Lux	117Lux	117Lux
Lux @ 3m 6500K	111Lux	111Lux	111Lux	54 Lux	54 Lux	54 Lux
Lux @ 1m Red	251Lux	251Lux	251Lux	175Lux	175Lux	175Lux
Lux @ 2m Red	82Lux	82Lux	82Lux	41Lux	41Lux	41Lux
Lux @ 3m Red	43Lux	43Lux	43Lux	19Lux	19Lux	19Lux
Lux @ 1m Green	663Lux	663Lux	663Lux	383 Lux	383 Lux	383 Lux
Lux @ 2m Green	210Lux	210Lux	210Lux	1010 Lux	1010 Lux	1010 Lux
Lux @ 3m Green	109Lux	109Lux	109Lux	47Lux	47Lux	47Lux
Lux @ 1m Blue	103Lux	103Lux	103Lux	60 Lux	60 Lux	60 Lux
Lux @ 2m Blue	38 Lux	38 Lux	38 Lux	16Lux	16Lux	16Lux
Lux @ 3m Blue	23 Lux	23 Lux	23 Lux	7Lux	7Lux	7Lux
Lumen Output 2700K	2700LM	2700LM	2700LM	1350LM	1350LM	1350LM
Lumen Output 3200K	2700LM	2700LM	2700LM	1350LM	1350LM	1350LM
Lumen Output 5600K	2850LM	2850LM	2850LM	1400LM	1400LM	1400LM
Lumen Output 6500K	2850LM	2850LM	2850LM	1400LM	1400LM	1400LM
Lumen Output Red	853LM	853LM	853LM	437LM	437LM	437LM
Lumen Output Green	234LM	234LM	234LM	120LM	120LM	120LM
Lumen Output Blue	358LM	358LM	358LM	183LM	183LM	183LM
Dimming	0-100%	0-100%	0-100%	0-100%	0-100%	0-100%
Special Effects	Storm, Flash,Candle,Color Cycle	Storm, Flash,Candle,Color Cycle	Storm, Flash,Candle,Color Cycle	Storm, Flash,Candle,Color Cycle	Storm, Flash,Candle,Color Cycle	Storm, Flash,Candle,Color Cycle
Max Power Consumption	32W	32W	32W	16w	16w	16w
Power Source	100-240V AC, 15V 3A DC	100-240V AC, 15V 3A DC	100-240V AC, 15V 3A DC	100-240V AC, 15V 3A DC	100-240V AC, 15V 3A DC	100-240V AC, 15V 3A DC
Compatible D-Tap Adapter	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket
Battery Compatibility	Built in	Built in	Built in	Built in	Built in	Built in
Charger	Built in	Built in	Built in	Built in	Built in	Built in
Charge Time to Full (Hours)	4	4	4	4	4	4
Charge Time to 80% (Hours)	3	3	3	3	3	3
Runtime @ 10% Brightness (Hours)	20	20	20	20	20	20
Runtime @ 50% Brightness (Hours)	4.4	4.4	4.4	4.4	4.4	4.4
Runtime @ 100% Brightness (Hours)	2.2	2.2	2.2	2.2	2.2	2.2
DMX Control	No	No	No	No	No	No
Wireless Control Type	2.4G, WIFI	2.4G, WIFI	2.4G, WIFI	2.4G, WIFI	2.4G, WIFI	2.4G, WIFI
Compatible Remote	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control	NanLite RC-1 Remote Control
Frequency	2.4ghz	2.4ghz	2.4ghz	2.4ghz	2.4ghz	2.4ghz
Compatible Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter	NanLite W-2 Wifi Adapter
Mount	T12 and 1/4 20" via adapter	T12 and 1/4 20" via adapter	T12 and 1/4 20" via adapter	T12 and 1/4 20" via adapter	T12 and 1/4 20" via adapter	T12 and 1/4 20" via adapter
Warranty	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )	Limited 2 Year Warranty (extend to 3 years total <a href="#">here</a> )

BE BRILLIANT.